



Product Features

- for hydraulic balancing of hot water return systems (PWH-C), supports thermal disinfection
- wetted metal parts made from dezincification-free, corrosion-resistant and lead-free gunmetal, resistant against aggressive water
- isolating unit with temperature sensor pocket
- PTFE seat gasket
- thermostatic balancing unit
- female pipe thread
- with plugged drain port
- free from dead spots

Standards and Approvals

- NSF/ANSI 61 & NSF/ANSI 372
- IAPMO/IGC 302

Technical data

- control range 122 °F - 149 °F
- pressure rating PN 16
- max. operating temperature 194 °F

Part no.	DN	A1	A2	H1 (mm)	H1 (in.)	H2 (mm)	H2 (in.)	L1 (mm)	L1 (in.)	T1 (mm)	T1 (in.)	cv (m³/h)	cv (GPM)	Weight (kg)	Weight (lbs)
1540201500	15	FPT 1/2	G 1/4	85	3,3	28	1,1	110	4,3	15	0,6	1,3	1,5	0,66	0,3
1540202000	20	FPT 3/4	G 1/4	85	3,3	33	1,3	123	4,8	16,3	0,6	1,6	1,9	0,85	0,39
1540202500	25	FPT 1	G 1/4	97,5	3,8	34	1,3	136	5,4	19,1	0,8	3,2	3,7	1,11	0,5