



Product Features

- for the hydraulic balancing of hot water circulation systems (PWH-C)
- consisting of a MULTI-THERM thermostatic circulation balancing valve, an anti-pollution check valve, and a stop valve
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- PTFE seat gasket
- thermostatic balancing unit
- incl. thermometer
- female pipe thread
- screw connection for non-destructive disassembly
- with a sealed drain connection
- free from dead spots

Standards and Approvals

- NSF/ANSI 61 & NSF/ANSI 372
- IAPMO/IGC 302

Technical data

- pressure rating PN 16
- max. operating temperature 194 °F

Part no.	DN	A1	A2	A3	H1 (mm)	H1 (in.)	H2 (mm)	H2 (in.)	L1 (mm)	L1 (in.)	L2 (mm)	L2 (in.)	T1 (mm)	T1 (in.)	T2 (mm)	T2 (in.)	T3 (mm)	T3 (in.)	Weight (kg)
1541201500	15	1/2-14 NPT	1/2-14 NPT	G 1/4	85	3,3	29	1,1	209	8,2	109	4,3	14,5	0,6	15	0,6	53,5	2,1	1,34
1541202000	20	3/4-14 NPT	3/4-14 NPT	G 1/4	84	3,3	34,5	1,4	231	9,1	121	4,8	16,5	0,6	16,3	0,6	53,5	2,1	1,66
1541202500	25	1-11 1/2 NPT	1-11 1/2 NPT	G 1/4	96,5	3,8	35,5	1,4	256	10,1	135,5	5,3	18	0,7	19,1	0,8	53,5	2,1	2,35

Part no.	Weight (lbs)
1541201500	0,61
1541202000	0,75
1541202500	1,06