



Product Features

- for hydraulic balancing of hot water return systems (PWH-C)
- wetted metal parts made from dezincification-free, corrosion-resistant and lead-free gunmetal, resistant against aggressive water
- PTFE seat gasket
- maintenance-free spindle gasket with self-lubricating EPDM lip gasket
- female pipe thread
- with plugged drain port
- incl. thermometer
- with pocket for temperature sensor Pt1000
- free from dead spots
- keeps throttle pre-setting when vale is closed and opened
- with indicator for pre-setting

Standards and Approvals

- NSF/ANSI 61 & NSF/ANSI 372
- IAPMO/IGC 302

Technical data

- pressure rating PN 16
- max. operating temperature 212 °F

Part no.	DN	A1	A2	A3	D1 (mm)	D1 (in.)	H1 (mm)	H1 (in.)	L1 (mm)	L1 (in.)	T1 (mm)	T1 (in.)	T2 (mm)	T2 (in.)	cv (m³/h)	cv (GPM)	Weight (kg)	Weight (lbs)
1556G01500	15	FPT 1/2	FPT 1/2	G 1/4	75.5	3.0	116	4.6	182.4	2.8	15	0.6	15	0.6	4.48	5.2	0.56	0.26
1556G02000	20	FPT 3/4	FPT 3/4	G 1/4	75.5	3.0	123	4.8	197.1	3.1	16.3	0.6	16.3	0.6	6.28	7.3	0.75	0.34
1556G02500	25	FPT 1	FPT 1	G 1/4	75.5	3.0	130	5.1	229.8	3.8	19.1	0.8	19.1	0.8	10.81	12.6	1.00	0.45
1556G03200	32	FPT 1 1/4	FPT 1 1/4	G 1/4	75.5	3.0	131	5.2	250.9	4.3	21.4	0.8	21.4	0.8	15.56	18.2	2.19	0.63
1556G04000	40	FPT 1 1/2	FPT 1 1/2	G 1/4	75.5	3.0	138	5.4	273.5	5.1	21.4	0.8	21.4	0.8	19.19	22.5	3.02	0.82
1556G05000	50	FPT 2	FPT 2	G 1/4	75.5	3.0	150	5.9	308.6	5.7	25.7	1.0	25.7	1.0	20.72	24.2	2.50	1.13

© Copyright by Kemper Water Control Systems, Inc., 2378 Linwood Ave. Naples, FL 34112, USA