



Product Features

- for connection to the building management system (BMS)
- wetted metal parts made from dezincification-free, corrosion-resistant and lead-free gunmetal, resistant against aggressive water
- including 2-wire Pt1000 temperature sensor
- full bore
- female pipe thread
- free from dead spots

Standards and Approvals

- NSF/ANSI 61 & NSF/ANSI 372
- IAPMO/IGC 302

Technical data

- pressure rating PN 16
- min. operating temperature 32 °F
- max. operating temperature 221 °F
- Class II power supply only
- length of connection cable 3.3 ft
- wire cross section 4 x 0.22 mm²
- diameter of the sensor 0.2 in

Part no.	DN	A1	A2	A3	H1 (mm)	H1 (in.)	L1 (mm)	L1 (in.)	L2 (mm)	L2 (in.)	T1 (mm)	T2 (mm)	Weight (kg)	Weight (lbs)
6270G01500	15	FPT 1/2	FPT 1/2	G 1/4	65	2,6	177,4	2,6	60	2,4	15	15	0,38	0,17
6270G02500	25	FPT 1	FPT 1	G 1/4	70,5	2,8	204,8	2,8	70	2,8	19,1	19,1	0,61	0,28
6270G03200	32	FPT 1 1/4	FPT 1 1/4	G 1/4	78	3,1	217,9	3,0	80	3,1	21,4	21,4	0,66	0,3
6270G05000	50	FPT 2	FPT 2	G 1/4	88,5	3,5	253,6	3,5	80	3,1	25,7	25,7	1,04	0,47